

PRODUCT2.80 mil Super Smooth Easy Release Coat Clear Polypropylene Overlaminates

DESCRIPTION

Film: Biaxially Oriented Polypropylene
Total Thickness: 2.80 mils
Film Thickness: 2.00 mils +/- 5%
Adhesive: Acrylic

FEATURES

- Ideal for overlay and labels with extended information
 - Excellent for use on tags and a variety of other substrates
 - Protects from moisture, abrasion, chemical, and oil resistance
 - Provides a quiet unwind and smooth surface
-

PHYSICAL PROPERTIES

Tensile Strength (LBS/IN)	30	PSTC*-131	(ASTM D3759**)
Elongation (% At Break)	180	PSTC-131	(ASTM D3759)
180° Peel Adhesion (OZ/IN)	23	PSTC-101	(ASTM D3330***)

APPLICATION TEMPERATURE32° F to 140° F

OPERATING TEMPERATURE

-10° F to 200° F nominal range. Contact your STA representative to determine actual temperature range specific to a particular application.

GOVERNMENT SPECIFICATIONSConforms to FDA regulations 21 CFR 175.105 and 21 CFR 177.1520

NOTES:

The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended the prospective user determine their suitability before adapting them on a commercial scale.

*Pressure Sensitive Tape Council

ASTM Standard D3759, "Standard Test Method for Tensile Strength and Elongation of Pressure-Sensitive Tapes," ASTM International, West Conshohocken, PA, www.astm.org*ASTM Standard D3330, "Standard Test Method for Peel Adhesion of Pressure-Sensitive Tape," ASTM International, West Conshohocken, PA, www.astm.org

Overlamination Division
6131 Knott Avenue, Buena Park, CA 90620
Phone: (714) 255-7888/(800) 258-8273 Fax: (714) 990-6851
www.sekisui-ta.com